



PICTURE	SIZE (MM) H*W	THICKNESS (MM)	PACKING (PCS/CTN)	MEASUREMENT (CM*CM*CM)	G.W. (KGS)	N.W. (KGS)
<p><b>WIRING DUCTS</b></p>	20*15	1,0	100	202*22*14	27	25,5
	20*20	1,0	100	202*11.5*26	29	28
	20*25	1,0	50	202*14*16	18,5	17,5
	25*25	1,0	50	202*14*18	19	18
	30*15	1,0	50	202*9*21	17	16
	30*20	1,0	50	202*12.5*21	17,5	16,5
	30*25	1.1-1.2	100	202*27*21	40	38
	30*30	1.1-1.2	50	202*16.5*21	19	18
	30*35	1.1-1.2	50	202*19*21	24	23
	30*40	1.1-1.2	50	202*21*21	27	25,5
	35*25	1.1-1.2	50	202*14*23	23	21,5
	35*30	1.1-1.2	50	202*16.5*23	23	22
	35*35	1.1-1.2	50	202*19*23	27	26
	35*40	1.1-1.2	50	202*21*23	28	27
	40*25	1.1-1.2	50	202*14*26	23	2
	40*30	1.1-1.2	50	202*16.5*26	26	25
	40*35	1.1-1.2	50	202*19*26	28,5	27,5
	40*40	1.1-1.2	50	202*21*26	29	28
	45*25	1.1-1.2	50	202*14*30	24,5	23,5
	45*45	1.2-1.3	50	202*24*30	34	33
	50*25	1.2-1.3	50	202*14*32	28	27
	50*30	1.2-1.3	100	202*16.5*32	29	28
	50*35	1.2-1.3	50	202*19*32	32	31
	50*40	1.2-1.3	50	202*21*32	34	32,5
	50*45	1.2-1.3	50	202*24*32	38	36
	50*50	1.3-1.4	50	202*27*32	40	39
	50*55	1.2-1.3	100	202*29*32	43	42
	50*60	1.2-1.3	50	202*31*32	46	44,5
	50*80	1.4-1.5	30	202*26*32	35	33
	50*100	1.4-1.5	30	202*32*32	44	42
	60*25	1.2-1.3	50	202*14*37	30	28
	60*35	1.2-1.3	50	202*19*37	35	33
	60*40	1.2-1.3	50	202*21*37	37	35
	60*45	1.3-1.4	50	202*24*37	41	39
	60*60	1.3-1.4	50	202*31*37	49	47
	65*25	1.2-1.3	50	202*14*40	32	30
65*35	1.2-1.3	50	202*19*40	37	35	
65*45	1.3-1.4	50	202*24*40	39	37	
65*65	1.4-1.5	30	202*35*25	28	26	
80*35	1.2-1.3	30	202*19*29	25	23,5	
80*40	1.2-1.3	30	202*21*29	27	25	
80*50	1.4-1.5	30	202*27*29	32	30	
80*60	1.4-1.5	30	202*31*29	34	32	
80*80	1.4-1.5	24	202*34*29	35	33	
80*100	1.4-1.5	24	202*42*29	37	35	
100*100	1.5-1.7	18	202*42*35	36	34	

Material: made of PVC, good insulation and heat-resistant p to 85°C.

Struction: make up of duct botton and lid, with two out-holes designed at the botton.

NOTE: Above allspec. for Height X Width, 2M/pc or 1M/PC.