

Pentax Electric Ltda

Sistema de Chamada para Elevadores (Wireless)



Pentax Electric Ltda

Vendas: Paulo Santos

Tel: (11) 98707-9652 / 4186-2981

Email: paulosantos@pentax-electric.com

PTX-HCM Transmitters—Feature and Specification

Distinguish Features

1. Use SAW DEVICE aeronautical communications device to ensure **stability of signal transmission**.
2. Super stability registration technology, **avoid garbled phenomenon**.
3. Built-in **anti-channel mixing** function.
4. Resistance against temperature and humidity changing. Safe and stable.
5. **Flexible Coding**. Coding could be changed at will
6. All the **text on the button could be changed** for different application.
7. Easy to be **placed on the table or fixed on the wall**.
8. Enhanced designed for durability.
9. Single circuit design.

Specifications:

Frequency: 433.92Mhz

Modulations: FM

Output Power: $\leq 10\text{mw}$

Frequency Deflection: 500khz

Codec: Registration

Compatibility: It can work with display receiver
and watch receiver



Long Range Transmitter – PTX – HCM101B

(Estoque)



White



Black

- HCM101--
1. Economic
 2. Popular
 3. 1500m coverage
 4. Wide Application



Silver



Wood



Coffee



key



waterproof base



double side glue



side



face

Features

Physical Dimension

60*60*30mm

Weight

50g (With battery)

Colors:

Black, white, wood, coffee, silver or customized

Control

Single call button

Transmission Range

1500 meters free field

Battery

23A12V

Battery life

Half of a year (50 calls in a day) (Final Result subject to the quality of your local battery)

Waterproof Base :Yes

BOTÃO DIGITAL (Wireless) PARA CHAMADA DO ELEVADOR MOD. PTX-HCM101B - UTILIZADO NO SISTEMA ELETRONICO DE CHAMADA SEM FIO.

PTX-HCM series Receivers

Distinguish Features

1. Delete Function: Manual Delete
2. Sound Category: 12 Music chords or Voice Alert
3. Level of sound: 1-6 grade
4. Display Time: 1-99 Seconds, infinite (Manual Delete)
5. English Letter Display: A B C D E F H P(80 letters)
6. Storage: 10 groups of numbers, Recycling Display
7. Put on the table or fixed on the wall freely

Compatible with
HCM series
transmitters

Specifications:

Frequency: 433.92Mhz

Modulation: FSK(FM)

Consumed Electricity: 50mA

Audio Output: 0-1.5W

Power Supply: AC100-220V/50-60HZ--
DC12V/1A

Receiving Sensibility:-108dbm

Antenna Type:External Antenna



(PTX-HCM3000 series)

Features

Dimension :240mm*140mm*35mm,Weight: 990g

Color: Black, Alert: 12 music, **no voice alert**



PTX-HCM13000B

Call No. 01-99



DISPLAY RECEPTOR (WIRELESS)
Mod. PTX-HCM13300B - MOSTRA 3
GRUPOS DE CHAMADAS AO MESMO
TEMPO COM 2 DÍGITOS -
TAMANHO 240*140*35 MM -
CHAMADA POR ALARME

PTX-HCM1330B (Estoque)

Show 3 groups of calling number at
same time



PTX-HCM13100B

Call No. 001-999



PTX-HCM3500

First 2 digits: Calling Number
01-99 or A1-P9

Last 1 digit: Function code

1-Order,2-Drink,6-Service,8-
Bill

(PTX-HCM14000B series)

Features

Dimension : 20.2*13*3cm,Weight: 950g

Color: Black, Alert: music, voice alert



DISPLAY RECEPTOR (WIRELESS) Mod. PTX-HCM14300B - MOSTRA 3 GRUPOS DE CHAMADAS AO MESMO TEMPO COM 2 DÍGITOS - TAMANHO 202*130*30MM - CHAMADA POR ALARME OU VOZ

PTX-HCM14300B (Estoque)

Show 3 groups of calling number at same time




PTX-HCM14500B

The 3 digits: Calling Number

001-999 or A01-P99



Produtos para Painéis de Automação Industrial

Bornes Mola e Parafuso	Acopladores a Relé	Fontes Chaveadas	Tomadas Multipolares	Contatores	Disjuntor Motor
					
Mini Disjuntores	Temporizadores	Botões 22mm	Botões de Comando	Botoneiras de Comando	Montagens Customizadas
					
Espiral em PVC	Plugs e Tomadas 3P+T	Chaves Seccionadoras	Bornes para PCB	Instrumentos de Medição	Horímetro
					
Terminais Cabos até 240mm	Conector em Barra	Canaletas em PVC	Ventiladores para Painéis	Caixas-ABS e Policarbonato	Ferramentas de Montagens
	